

SpringFlex SubFloor System

The professional standard for floating wood resilient permanent subfloors for use over concrete slabs and other hard surfaces. This subfloor is resilient and energy absorbent. Safety and performance at a great price.

21st century state-of-the-art basket weave subfloor system. Pre-manufactured from cross-laminated birch and recycled rubber. Allows for easy installation of a professional subfloor system

Finish/Surface

Combine with plywood (supplied by customer) and any of our rollout floors, or use hardwood

Life Expectancy

20 years

Guarantee

1-year guarantee against manufacturer defects

Specifications

Area-elastic floors offering from 51 to 71% shock absorption. Meets or exceeds DIN-V 18032.2 requirements. Construction height is only 75–77 mm (3"). 45° degree installation equally distributes energy.

Call Stagestep for a custom quote.

SpringFlex Beam Weight: 5.7 lbs (2.6 kg)

Hardwood Floor Weight: ~ 3 lbs/sf (1.63 kg/sqm)

At A Glance

- State-of-the-art basket weave system
- 20-year life expectancy
- 1-year guarantee



SpringFlex

Our Customers Say It Best

*"When we built Starwest Studios in Hollywood, a state of the art broadcast dance studio, before all the lights, cameras and action, we had to lay the foundation. That is when we decided to install the best, a 3800 square foot **Stagestep** sprung wood dance floor. Our choreographers expect only the best! Starwest Studios has the largest sprung wood floor in Los Angeles, including a marley sprung floor also from **Stagestep** with a white Cyc for filming dance."*

Sammy Oriti, Creative Director
Starwest Studios

To order, call in the U.S. (800) 523-0960 or Canada (866) 491-9019
(215) 636-9000 • stagestep.com • sales@stagestep.com